

## Radiateur-special



### Rubber radiator hose

Rubber radiator hose conform DIN 74311 with Red marking, resistance against anti-fries liquids

**Temperature** : -30 up/to + 130 gr. C

**Bursting Pressure** : 7 bar

**Tube** : EPDM Smooth Black

**Cover** : Neoprene with marking

Standard lengths of 1 metres

| Inside diameter | Outside diameter | W.P.  | Roll length | Partno:  |
|-----------------|------------------|-------|-------------|----------|
| 10 mm           | 16 mm            | 4 bar | 1 metres    | AWARS010 |
| 13 mm           | 20 mm            | 4 bar | 1 metres    | AWARS013 |
| 15 mm           | 22 mm            | 4 bar | 1 metres    | AWARS015 |
| 18 mm           | 25 mm            | 4 bar | 1 metres    | AWARS018 |
| 20 mm           | 27 mm            | 4 bar | 1 metres    | AWARS020 |
| 22 mm           | 29 mm            | 4 bar | 1 metres    | AWARS022 |
| 25 mm           | 32 mm            | 4 bar | 1 metres    | AWARS025 |
| 28 mm           | 36 mm            | 4 bar | 1 metres    | AWARS028 |
| 30 mm           | 38 mm            | 4 bar | 1 metres    | AWARS030 |
| 32 mm           | 40 mm            | 4 bar | 1 metres    | AWARS032 |
| 35 mm           | 43 mm            | 4 bar | 1 metres    | AWARS035 |
| 38 mm           | 48 mm            | 4 bar | 1 metres    | AWARS038 |
| 40 mm           | 50 mm            | 4 bar | 1 metres    | AWARS040 |
| 42 mm           | 52 mm            | 4 bar | 1 metres    | AWARS042 |
| 45 mm           | 55 mm            | 4 bar | 1 metres    | AWARS045 |
| 48 mm           | 58 mm            | 4 bar | 1 metres    | AWARS048 |
| 50 mm           | 60 mm            | 4 bar | 1 metres    | AWARS050 |
| 55 mm           | 65 mm            | 4 bar | 1 metres    | AWARS055 |
| 60 mm           | 70 mm            | 4 bar | 1 metres    | AWARS060 |
| 65 mm           | 75 mm            | 4 bar | 1 metres    | AWARS065 |
| 70 mm           | 80 mm            | 4 bar | 1 metres    | AWARS070 |
| 75 mm           | 85 mm            | 4 bar | 1 metres    | AWARS075 |
| 80 mm           | 90 mm            | 4 bar | 1 metres    | AWARS080 |
| 90 mm           | 102 mm           | 4 bar | 1 metres    | AWARS090 |
| 100 mm          | 112 mm           | 4 bar | 1 metres    | AWARS100 |
| 110 mm          | 122 mm           | 4 bar | 1 metres    | AWARS110 |
| 120 mm          | 134 mm           | 4 bar | 1 metres    | AWARS120 |

## Tubano



### Tubano Radiateurslang / Radiatorhose

Geschikt voor water, lichte zuren en logen.

Ozon-, warmte- en oliebestendig.

Used for water, restricted chemical resistance.

Ozon-, heat-, oil resistance.

Temperature: -30°C tot +120°C

Standard length: 1 meter

| Ø I.D.  | Uitzettingsvermogen | WP at 20° C. | buigradius | Partno: |
|---------|---------------------|--------------|------------|---------|
| 20 mm   | 20 - 25 mm          | 1,5 bar      | 70 mm      | ATUB020 |
| 25 mm   | 25 - 31 mm          | 1,5 bar      | 85 mm      | ATUB025 |
| 31,5 mm | 31,5 - 36 mm        | 1,5 bar      | 105 mm     | ATUB032 |
| 33,5 mm | 33,5 - 38 mm        | 1,5 bar      | 110 mm     | ATUB034 |
| 37 mm   | 37 - 44 mm          | 1,5 bar      | 115 mm     | ATUB037 |
| 44 mm   | 44 - 48 mm          | 1,5 bar      | 120 mm     | ATUB044 |
| 48 mm   | 48 - 55 mm          | 1,5 bar      | 125 mm     | ATUB048 |
| 55 mm   | 55 - 65 mm          | 1,5 bar      | 130 mm     | ATUB055 |
| 65 mm   | 65 - 75 mm          | 1,5 bar      | 140 mm     | ATUB065 |