

Vinylon - Jamaica



Plat oprolbare slang, zeer licht, hoge drukbestendigheid. Ruimte bij gebruik, transport en opslag. Temperatuurbereik: -10° C + 60° C.

Specifications: using advanced technology this layflat hose provides the benefit of high performance with lightness in weight, when compared with same sizes

Of spiral PVC delivery hoses and rubber discharge hoses. Additionally it is easier to store, to handle and to transport. Temperature range: -10° C + 60° C.

Gladde naadloze zwarte binnenwand. Hoge treksterkte, gladde buitenwand, zeer sterke hechting tussen binnen- en buitenlagen.

Structure: smooth and seamless black inner surface, particularly resistant to elongation, smooth cover. Very high adhesion between inner and outer layers.

Diameter	WD bij 20°C	Rollengte	Artikelno:
020	10 bar	100 meter	CFLVM020
025	10 bar	100 meter	CFLVM025
032	10 bar	100 meter	CFLVM032
038	10 bar	100 meter	CFLVM038
050	10 bar	100 meter	CFLVM050
065	8 bar	100 meter	CFLVM065
076	8 bar	100 meter	CFLVM075
102	8 bar	100 meter	CFLVM100
127	6 bar	100 meter	CFLVM125
153	4 bar	100 meter	CFLVM150
204	2.5 bar	50 meter	CFLVM200

Tricotech – Soleil



Temperatuurbereik: -5°C + 60°C. Zeer zachte slang. Slijtvast en bestand tegen plotselinge temperatuursveranderingen, verouderingsbestendig.

Temperature range: -5°C + 60°C. Extremely soft. Good resistance to abrasion and sudden temperaute changes. Excellent wheater resistance

Binnenwand is van PVC, levensmidelenbestendig. Buitenwand is van PVC. Inlage van gebreid polyester.

Lined in non-toxic PVC. Outer surface in PVC. Knitted textile reinforcement. Circular cross-section.

Diameter inwendig	Diameter uitwendig	Wdruk bar	Rollengte meter	Artikelno:
12,5 mm	17,5 mm	12 bar	25,50	CWATO012
15 mm	20 mm	12 bar	50	CWATO015
19 mm	25,5 mm	12 bar	25,50	CWATO019
25 mm	33 mm	8 bar	50	CWATO025
30 mm	38 mm	10 bar	50	CWATO030
40 mm	48 mm	8 bar	50	CWATO040
50 mm	63 mm	8 bar	25	CWATO050