

EUROSTAR VIZ Brandslang, type VIZ - Fire hoses VIZ



Zeer geschikt voor toepassing in de industrie, bouw, landbouw, scheepvaart en pompenindustrie



Eurostar@ brandslangen, kleur wit, type VIZ, vervaardigd van hoogwaardige synthetische garens en een EPDM rubberlining, rot- en schimmelvrij, bestand tegen lage en hoge temperaturen, ozon, weersinvloeden en lichte concentraties chemicaliën. rollengte 20 meter, maximaal 80 meter, Overige lengten op aanvraag.

Conformiteit : Scheepvaart en BS Class I

Standard coil length 20 mtr, up to 80 mtrs, outside: synthetic woven textile reinforcement, inside: High tensile synthetic rubber, Maintenance free; do not need drying, Unaffected by mildew, Excellent resistance against ozone and Rot-proof .

According to: Navigation - BS Class I

Inches	mm	WP	BP	Part.no.
1	25 mm	17 bar	50 bar	EVIZ0250
1.1/4	32 mm	17 bar	50 bar	EVIZ0320
1.1/2	38 mm	17 bar	50 bar	EVIZ0380
1.3/4	45 mm	17 bar	50 bar	EVIZ0450
2	52 mm	17 bar	50 bar	EVIZ0500
2.1/2	65 mm	17 bar	50 bar	EVIZ0650
2.3/4	70 mm	15 bar	50 bar	EVIZ0700
3	75 mm	15 bar	50 bar	EVIZ0750
3.1/2	90 mm	10 bar	45 bar	EVIZ0900
4	100 mm	10 bar	35 bar	EVIZ1000
4.1/2	110 mm	10 bar	35 bar	EVIZ1100
5	125 mm	10 bar	30 bar	EVIZ1250
6	152 mm	10 bar	30 bar	EVIZ1500
8	200 mm	5 bar	15 bar	EVIZ2000

EUROSTAR RMC



Brandslang, type RMC/VCZ - Fire hoses RMC/VCZ

Eurostar@ brandslangen, kleur Wit, type VCZ, vervaardigd van hoogwaardige synthetische garens en een EPDM rubberlining, rot- en schimmelvrij, bestand tegen lage en hoge temperaturen, ozon, weersinvloeden en lichte concentraties chemicaliën. rollengte 20 meter, maximaal 80 meter, Overige lengten op aanvraag. Conformiteit : DIN 14811 - NBN S21-024 BS Scheepvaart en BS Class I - **Veritas MED gecertificeerd**

Standard coil length 20 mtr, up to 80 mtrs, outside: synthetic woven textile reinforcement, inside: High tensile synthetic rubber, Maintenance free; do not need drying, Unaffected by mildew, Excellent resistance against ozone and Rot-proof .

According to: DIN 14811 - NBN S21-024 BS Scheepvaart en BS Class I - **Veritas MED gecertificeerd**

Vertias MED approved



You can download the certificate from our website : www.eteha.nl



Inches	mm	WP	BP	Part.no.
1	25 mm	20 bar	50 bar	ERZC0250
1.1/4	32 mm	20 bar	50 bar	ERZC0320
1.1/2	38 mm	20 bar	50 bar	ERZC0380
1.3/4	45 mm	20 bar	50 bar	ERZC0450
2	52 mm	20 bar	50 bar	ERZC0500
2.1/2	65 mm	20 bar	50 bar	ERZC0650
2.3/4	70 mm	20 bar	50 bar	ERZC0700
3	75 mm	15 bar	50 bar	ERZC0750
3.1/2	90 mm	15 bar	45 bar	ERZC0900
4	100 mm	15 bar	45 bar	ERZC1000
4.1/2	110 mm	15 bar	45 bar	ERZC1100
5	125 mm	15 bar	40 bar	ERZC1250
6	152 mm	15 bar	40 bar	ERZC1500
8	200 mm	14 bar	42 bar	ERZC2000