

## Sheeting in rolls



To guarantee that we can meet the needs of our customers, **Watsonia bv - Stanstechniek** has a wide range of different qualities in stock made in following polymers. Qualities which are not in stock can be made to order.

Available:  
Sheeting in rolls  
Packing die cut to your specification  
Ribbed matting in rolls  
Entrance mats  
Flooring

### SBR-rubberplaat - 150 SBR-rubbersheeting - 150

<b>S.G.</b>	: ca 1,50
<b>Hardheid</b>	: 70 graden shore A +/- 5%
<b>Treksterkte</b>	: ca 40 kg/cm <sup>2</sup>
<b>Rek bij breuk</b>	: ca 250%
<b>Kleur</b>	: Zwart
<b>Temperatuur</b>	: -10 tot +50° C.
<b>Uitvoering</b>	: beide zijden glad
<b>Rol-afmetingen</b>	: 2 t/m 6 mm = 10 x 1,20 mtr 8 t/m 20 mm = 5 x 1,20 mtr

- Quality SBR
- Colour BLACK
- Execution both sides smooth
- Specific gravity 1.50
- Hardness 70 Shore A
- Tensile strength 4 Mpa
- Elongation at break 250 %
- Temperature -10/+70°C
- Dimensions 1 mm till 6 mm : 10 m x 1.20 m
- 8 mm till 20 mm : 5 m x 1.20 m
- Available with and without insertions

### Neopreen-rubberplaat - 145 CR-rubbersheeting - 145

<b>S.G.</b>	: ca 1,45
<b>Hardheid</b>	: 65 graden shore A +/- 5%
<b>Treksterkte</b>	: ca 65 kg/cm <sup>2</sup>
<b>Rek bij breuk</b>	: ca 220%
<b>Kleur</b>	: Zwart
<b>Temperatuur</b>	: -40 tot +100° C.
<b>Uitvoering</b>	: beide zijden glad
<b>Rolafmeting</b>	: 1 t/m 6 mm = 10 x 1,20 mtr 8 t/m 10 mm = 5 x 1,20 mtr

- Quality CR
- Colour BLACK
- Execution both sides smooth
- Specific gravity 1.45
- Hardness 65 Shore A
- Tensile strength 5,5 Mpa
- Elongation at break 250 %
- Temperature -25°/+90°C
- Dimensions 1 mm till 6 mm : 10 m x 1.35 m
- 8 mm till 10 mm : 5 m x 1.40 m
- Available with and without insertions



### NBR-rubberplaat - 160 NBR-rubbersheeting - 160

<b>S.G.</b>	: ca 1,40
<b>Hardheid</b>	: 65 graden shore A +/- 5%
<b>Treksterkte</b>	: ca 40 kg/cm <sup>2</sup>
<b>Rek bij breuk</b>	: ca 200%
<b>Kleur</b>	: Zwart
<b>Temperatuur</b>	: -25 tot +90° C.
<b>Uitvoering</b>	: beide zijden glad
<b>Rol-afmetingen</b>	: 1 t/m 6 mm = 10 x 1,35 mtr 8 t/m 10 mm = 5 x 1,40 mtr

- Quality NBR
- Colour BLACK
- Execution both sides smooth
- Specific gravity 1.40
- Hardness 65 Shore A
- Tensile strength 4 Mpa
- Elongation at break 200 %
- Temperature -25/+90°C
- Dimensions 1 mm till 6 mm : 10 m x 1.35 m
- 8 mm till 10 mm : 5 m x 1.40 m
- Available with and without insertions