

## Matting in rolls



To guarantee that we can meet the needs of our customers, **Watsonia bv - Stanstechniek** has a wide range of different qualities in stock made in following polymers. Qualities which are not in stock can be made to order.

Available:  
Sheeting in rolls  
Packing die cut to your specification  
Ribbed matting in rolls  
Entrance mats  
Flooring

### Matting 50 Kv Matting 50 Kv

#### SWITCH BOARD MATTING

- Tested by "Elektrisches Prüfamt" in München, report no. 97024 according to the German specification VDE 0303.
- Resistant to 50.000 V
- Marking on backside "Isoliermatte gepr. nach VDE 0303-50.000 Volt"
- Backside with cloth impression
- Hardness 65° Shore A
- Colour grey
- Thickness 4,5 mm ribbed surface
- Dimensions 10 m x 1,20 m or 10 m x 1,00 m
- Thickness 4 mm smooth surface
- Dimensions 10 m x 1,00 m
- 

### Matting 20 Kv Matting 20 Kv

#### SWITCH BOARD MATTING

- Tested by "Elektrisches Prüfamt" in München, report no. 97024 according to the German specification VDE 0303.

- Resistant to 20.000 V
- Marking on backside "Isoliermatte gepr. nach VDE 0303-20.000 Volt"
- Backside with cloth impression
- Hardness 65° Shore A
- Colour grey
- 
- Thickness 4,5 mm ribbed surface
- Dimensions 10 m x 1,20 m or 10 m x 1,00 m
- 
- Thickness 4 mm smooth surface
- Dimensions 10 m x 1,00



### Matting 1000 v Matting 1000 v

#### SWITCH BOARD MATTING

- Tested by "Elektrisches Prüfamt" in München, report no. 97024 according to the German specification VDE 0303.
- Resistant to 1.000 V
- Marking on backside "Isoliermatte gepr. nach VDE 0303-1.000 Volt"
- Both sides smooth
- Hardness 50° Shore A
- Colour orange
- 
- Thickness 1,6 mm
- Dimensions 10 m x 1,20 m or 10 m x 1,00 m
- 

