eteha HOSE SPECIALIST

De flexibele oplossing

Spiraflex PP 80

Heating and Ventilation Ducting

Description

Antistatic, flexible (fan) spiral hose for medium temperature range made of antistatic PVC-coated polyester fabric and with a spring steel spiral covered by scuff protection. A finely crafted specialist sewn product of high quality using high-grade raw materials. Highly suitable for conveying gaseous media in areas where static charge buildup is to be avoided. Temperature range: -20°C to +100°C

Properties

- Antistatic 10 6 OHMS
- Smooth interior
- High tensile strength
- Good compression capability
- Large diameters available
- Spiral-free sleeves
- Lightweight
- Durable • Highly flexible
- Non-kinking
- With scuff protection
- Continuous connection possible

Spiraflex PP 80		
diameter inside	**weight**	**Pressure**
mm	kg/m	bar
152	0.28	0.64
180	0.29	0.6
203	0.30	0.55
229	0.32	0.5
254	0.34	0.45
305	0.36	0.35
357	0.46	0.3
408	0.51	0.25
425	0.69	0.24
457	0.74	0.23
508	0.82	0.2
525	0.98	0.19
560	1.05	0.18
600	1.12	0.17
700	1.40	0.15
800	1.70	0.13
900	2.10	0.11
1000	2.50	0.1

Eteha bv – Slangtechniek
Papendrecht - Netherlands
tel. +31 - (0)88 – 66 55 800
fax +31 - (0)88 – 66 55 801
website : www.eteha.nl
email : eteha@eteha.nl